

PRODUCT DATASHEET

TubeKIT LED 1500mm 21.5W 4000K

TubeKIT™ | Mobile LED batten luminaire



Areas of application

- Indoor applications
- Corridors, entrance areas, stairwells, living rooms, basements
- Shelves, furniture integration or under cabinet mounting
- Direct or indirect lighting (e.g. cove lighting)
- Kitchens, workspaces

Product benefits

- Easy to use and multifunctional LED batten luminaire
- All required accessories included (screws, dowels, brackets, hook)
- Ready for connection due to integrated on/off switch and cable with EU-plug
- Bright, robust and durable
- Energy savings of up to 65 % comp. to luminaires using T8 fluorescent lamps on CCG
- Homogeneous light output

Product features

- Durable and energy-saving LED luminaire
- Mercury-free and RoHS compliant
- Clip-In technology for stationary use and hook for mobile use
- Lifetime: up to 30,000 h
- Not dimmable
- Polycarbonate housing
- Uniform illumination



- Color temperatures: 3,000 K, 4,000 K
- Color rendering index $R_a \geq 80$

TECHNICAL DATA

Electrical data

| | |
|------------------------|-------------|
| Nominal wattage | 21.50 W |
| Nominal voltage | 220...240 V |
| Mains frequency | 50...60 Hz |
| Power factor λ | ≥ 0.90 |
| Protection class | II |

Photometrical data

| | |
|--|------------|
| Luminous flux | 2365 lm |
| Total luminous flux of contained light sources | 2600 lm |
| Luminous efficacy | 110 lm/W |
| Color temperature | 4000 K |
| Light color (designation) | Cool White |
| Color rendering index Ra | > 80 |
| Beam angle | 150 ° |

Dimensions & Weight

| | |
|----------------|------------|
| Length | 1500.00 mm |
| Width | 35.00 mm |
| Height | 36.50 mm |
| Product weight | 382.00 g |
| Cable length | 1800 mm |



TUBEKITLED 1.5 G5

Materials & Colors

| | |
|-----------------|--------------------|
| Body material | Polycarbonate (PC) |
| Mercury content | 0.0 mg |

Application & Mounting

| | |
|---------------------------|--------------|
| Ambient temperature range | -20...+45 °C |
|---------------------------|--------------|

| | |
|-------------------------|------------------|
| Type of connection | Plug type C (EU) |
| Type of protection | IP20 |
| Dimmable | No |
| Mounting type | Surface |
| Mounting location | Ceiling / Wall |
| Application environment | Indoor |
| LED module replaceable | Not replaceable |
| With light source | Yes |
| Holder designation | G5 |

Lifespan

| | |
|----------------------------|-------|
| Number of switching cycles | 15000 |
|----------------------------|-------|



Certificates & Standards

| | |
|--|----------|
| Standards | CE / EAC |
| Luminaire with limited surface temperature, "D sign" | No |

EQUIPMENT / ACCESSORIES

– Complete mounting and connecting accessories included

DOWNLOAD DATA

| Documents and certificates | Document name |
|--|----------------------------|
|  User instruction | TUBEKIT LED |
|  Declarations Of Conformity CE | CE Declaration TubeKit LED |

LOGISTICAL DATA

| Product code | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume |
|---------------|------------------------------|--------------------------------------|--------------|-----------------------|
| 4058075265097 | Folding box 1 | 38 mm x 71 mm x 1,529 mm | 568.00 g | 4.13 dm ³ |
| 4058075265103 | Shipping box 8 | 1,550 mm x 210 mm x 195 mm | 5402.00 g | 63.47 dm ³ |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.