



Specifications Noxion LED Panel Delta Pro V3 30W 3960lm - 830 Warm White | 60x60cm - UGR <22 - Philips Xitanium Driver - Emergency 3H

[View Product](#)

## General Information

|                          |  |
|--------------------------|--|
| SKU                      | 242310   |
| EAN                      | 8719157034852  |
| Brand                    | Noxion   |
| Manufacturer Name        | Noxion LED Panel Delta Pro V3 30W 3960lm 3000K 600*600 UGR<22 (4x18W eqv.) + emergency integration |
| Any Lamp all-in warranty | 6 Years  |
| Average Lifetime (h)     | 50000  |
| Series                   | Delta Pro  |

## Technical Information

|                             |                   |
|-----------------------------|-------------------|
| Technology                  | LED Integrated    |
| Voltage (V)                 | 220-240           |
| Dimmable                    | Not Dimmable      |
| Colour Code                 | 830 Warm White    |
| Colour temperature (Kelvin) | 3000 Warm White   |
| Colour Rendering (Ra)       | 80-89             |
| Colour of Light             | White             |
| Light colour options        | Single Color      |
| Luminous Efficacy (lm/W)    | 132               |
| IP-rating                   | IP20              |
| Impact Protection (IK)      | IK03 - 0.35 joule |

|                    |               |
|--------------------|---------------|
| Fixture Connection | Push Terminal |
|--------------------|---------------|

|                     |         |
|---------------------|---------|
| Finish of Reflector | Frosted |
|---------------------|---------|

|              |       |
|--------------|-------|
| Power factor | >0.90 |
|--------------|-------|

|                       |           |
|-----------------------|-----------|
| Product Type Category | LED Panel |
|-----------------------|-----------|

## Fixture Information

|                 |          |
|-----------------|----------|
| Mounting Method | Recessed |
|-----------------|----------|

|                      |                          |
|----------------------|--------------------------|
| Unified Glare Rating | < 22 - for general areas |
|----------------------|--------------------------|

|               |                  |
|---------------|------------------|
| Optical Cover | PS (Polystyrene) |
|---------------|------------------|

|                       |            |
|-----------------------|------------|
| Operating Temperature | +10 to +45 |
|-----------------------|------------|

|                    |                    |
|--------------------|--------------------|
| Emergency Lighting | 1H Emergency Light |
|--------------------|--------------------|

|                       |       |
|-----------------------|-------|
| Colour of the Fixture | White |
|-----------------------|-------|

|         |           |
|---------|-----------|
| Housing | Aluminium |
|---------|-----------|

|                    |       |
|--------------------|-------|
| Colour of material | White |
|--------------------|-------|

## Dimensions

|                |         |
|----------------|---------|
| LED panel size | 60x60cm |
|----------------|---------|

|             |     |
|-------------|-----|
| Length (mm) | 595 |
|-------------|-----|

|            |     |
|------------|-----|
| Width (mm) | 595 |
|------------|-----|

|             |    |
|-------------|----|
| Height (mm) | 10 |
|-------------|----|

## Sensor Information

|                |  |
|----------------|--|
| Type of sensor |  |
|----------------|--|

### Why Any-lamp?

No Sensor



Order from the **largest lighting specialist** in Europe



**Customised** quotation



Up to **7 years warranty**



**Easy** return process